Relay Sockets ES152N Series – Datasheet


Bremas type: ES152NCNER

Mechanical data	
Max. torque on the screws	0,8 Nm - 7 in.lb
Wire section solid and stranded	Min 0,5 mm ² – AWG 20
	Max 2,5 mm ² – AWG 14
Weight	66g
Wire strip	
Lenght	7mm
Electrical data:	
Terminal protection degree	IP 20
Rated voltage IEC	300 V AC
Rated current IEC	12 A
Rated voltage UL	300 V AC
Rated current UL	10 A (or 12 A at 150 V AC)
Thermal data	
Operating temperatures	-25°C… + 85°C
Conformity	
RoHS compliant (Directive 2011/65/EU and Delegated Directive 2015/863)	






Wire locking system




Dimensions

Measures in (mm)



Electrical scheme



Bremas Ersce SpA Via castellazzo 9 - 20040 Cambiago (MI) Tel +39 02 95651611 Fax +39 02 95651639 www.bremas.eu info@bremas.it ISO 9001 Certified Quality System

© 2016 Copyright Brenss Encos. Subject to change without notice and errors excepted. Data reported in this paper are carefully checked and represent hybrical values of series production. The descriptions of the device and its applications, contractions of exact the area in the feature descriptions of use device land its applications, contractions of the device and its applications, contractions or the descriptions of the device and its applications, contractions of the devi

27