Relay Sockets ES353S Series – Datasheet

Bremas Ersce SpA Via castellazzo 9 - 20040 Cambiago (MI) Tel +39 02 95651611 Fax +39 02 95651639 www.bremas.eu info@bremas.it ISO 9001 Certified Quality System

Bremas type: ES353SCNER

Mechanical data	
Max. torque on the screws	0,8 Nm - 7 in.lb
Wire section solid and stranded	Min. 0,5 mm ² – AWG 20
	Max 2,5 mm ² – AWG 14
Weight	36g
Wire strip	
Lenght	7 mm
Electrical data:	
Terminal protection degree	IP 20
Rated voltage IEC	300 V AC
Rated current IEC	12 A
Rated voltage UL	150 V AC
Rated current UL	12 A
Thermal data	
Operating temperatures	-25°C + 85°C
Conformity	
RoHS compliant (Directive 2 2015/863)	011/65/EU and Delegated Directive




Dimensions Measures in (mm)




BREMAS

Wire locking system



Electrical scheme



© 2016 Copyright Bremas Ersce. Subject to change without notice and errors excepted. Data reported in this paper are carefully checked and represent typical values of series production. The descriptions of the device and its applications, contexts of use, details of external controls, information on installation and operation are provided to the best of our knowledge. In any case, this does not mean that the features described may derive legal responsibilities that extend beyond the "Terms and Conditions" of Bremas Ersce. The customer / user is not absolved from the obligation to examine our information and recommendations and the relevant technical regulations before using the products for their own purposes.

7.6